



- ◆ High Definition Picture Quality
- ◆ 4CH HD-SDI Camera Input Support
720P/1080P Resolution
- ◆ True Real-Time Triple Streaming for Live
Display, Playback and Recording
- ◆ Trouble Free DDNS Setup
- ◆ Fully Control DVR via Network
- ◆ Maximum 6 SATA Devices
- ◆ Free CMS Support
- ◆ HDMI Output

SPECIFICATION

Model		LDVR-4HD
Camera Input		4CH
Video	HDMI	1 (Video Output [1024x768, 1280x1024, 1366x768, 1440x900] + Audio Output)
	Input	4 x HD-SDI
	Output	1VGA (1024x768, 1280x1024, 1366x768, 1440x900) + 1BNC (720x480 / 720x576) for SPOT Monitor
Audio	Input	4 HD-SDI
	Output	2 RCA
System	Operating System	Embedded Linux OS
	Internal HDD	Supports Max. x 6 SATA Devices (HDDx6, HDDx5+eSATAx1, HDDx5+DVDx1, HDDx4+DVDx1+eSATAx1)
	External HDD	YES (eSATA)
	Sensor In (NO, NC) Relay Out	Sensor-in x 4 Relay-out x 4
	Serial Interface	RS-485
	USB	2 x USB2.0
	Dimension (mm)	442(w)x92(h)x438(d)
	Weight (w/o HDD/ DVD±RW)	5KG
	Power	110V/220V
	Power Source	220W
Display	Speed	1080p/720p 120fps
	Split Screen	1,4, SEQ.
	Auto Channel Switching	Switching time : 1 ~ 99 sec
	Mode	Zoom (Digital x2~ x8), PIP, Auto SEQ.

SPECIFICATION

Model		LDVR-4HD	
Camera Input		4CH	
Recording	Compression		H.264 ASP (Internet Transmission: H.264)
	Dual Stream Resolution (Pixel)	Main (Recording)	1920 x 1080, 1280 x 720
		Sub (Network)	640 x 360
	Picture Quality		10~100 levels for adjustment
	Mode		Manual, Motion, Sensor, Schedule
	Speed		60 fps (1920 x 1080) 120 fps (1280 x 720)
	Pre-Alarm		1 ~ 10 SEC
	Post-Alarm		1 ~ 100 SEC
	Watermark		YES
Playback	Display		1, 4
	Search Mode		Date, time, event, camera
	Zoom		Digital (x2 ~ x8)
	Snapshot		YES
	Speed		Seek, Normal, REW & FF, Frame to Frame, Pause
	Device		Int. HDD
Network	Network Interface		10/100 Ethernet
	Protocol		TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP
	Application		Windows XP/VISTA/7(PC Client system)
	Remote Software		Licensed Application Software, IE Browser
	Account		1 Admin + 8 Users
	CMS		Yes
	3G / GPRS		Symbian, Windows Mobile, Blackberry, iPhone, Android phone
	Event Transport		E-mail

SPECIFICATION

Model		LDVR-4HD
Camera Input		4CH
Backup	Interface	USB 2.0 or SATA
	Audio Backup	YES
	Network	YES
	Backup Device (Optional)	Network Backup / USB Flash Drive / USB DVD±RW/ SATA DVD±RW
Alarm	Motion Detection	Detected Frames: Unlimited / Channel
		Sensitivity : 100 levels for each channel
		Area : Programmable individually
	Search (Event Criterion)	YES
Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)	
OSD & DVR Control	GUI	16-bit True Color
	Multi-Language	English, Traditional Chinese, Others
	Camera Title	Multi-Language
	USB Mouse	YES
	Touch Panel	Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)
	Remote Controller	IR Remote Control (Max. 4 Device)
	System Upgrade	via USB / Network
	Pan/Tilt/Zoom Control	Control From RS-485 Interface (Pelco P, Pelco D, Samsung, LG, LiLin)